



QUREACC BiDD

Bismuth Dimethyl Dithiocarbamate

CAS No : 21260-46-8
Molecular Formula : $C_9H_{18}BiN_3S_6$
Molecular weight : 569.60

SALES SPECIFICATIONS:

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Coarse Bright Yellow Powder
Loss On Drying (40°C)	%	0.5 Max.
Bismuth Content	%	35.0 - 38.0

APPLICATION

Bismuth Dimethyl Dithiocarbamate is accelerator used along with MBTS and Sulphur for High Temperature (160°C), High Speed Vulcanization of NR and SBR Rubbers. It is Primarily used in Wire and Cables Vulcanization of NR, SBR at High Temperature for Short Time.

PACKING AND STORAGE

Available in 25 kg Drum
To be stored in a clean, cool and dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713
Phase III, G.I.D.C
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 – 2420896 / 2423896

Rev.02 DT.05.05.2017