



QUREACC TST

2,4,6-trimercapto-s-triazine

CAS RN : 17766-26-6

SALES SPECIFICATION

| | |
|---------------------------|------------------------------------|
| Appearance | Light Yellow Powder |
| Heating Loss | 0.50% |
| Ash | 0.30% |
| Fineness (75 µm retained) | 0.50% |
| Solubility | Soluble in THF, insoluble in water |

APPLICATION

Qureacc TST is used for curing Acrylic Rubber, (ACM) Epichlorohydrin Rubber (ECO) and Chlorobutyl Rubber (CIIR).

It gives very good scorch safety without affecting cure rate. Gives excellent physical properties.

Dosage levels 0.5 to 1.5 phr.

PACKING AND STORAGE

Available in 10/20 Kg. Paper Bag

To be stored in a clean cool place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

OFFICE

31-H, LAXMI INDL.ESTATE,
NEW LINK ROAD, ANDHERI (W)
MUMBAI 400 053. INDIA
TEL : 91-22-66929152, 66929153,26310350
FAX : 91 - 22 - 66929154
E-Mail.: info@yashoindustries.com
Website: www.yashoindustries.com

FACTORY

PLOT NO.1713,
PHASE III, G.I.D.C.,
VAPI - 396 195.
GUJARAT, INDIA.
TEL. :-91 (260) 2420896 / 2423896
FAX :-91 (260) 2423996

Rev. DT.16.03.2015