

YALUB –DM 86

2,5-dimercapto-1,3,4-thiadiazole derivative

CAS Nr: 13539-13-4

SALES SPECIFICATION

Appearance	Clear Amber Liquid
Density @ 20°C	1.0200 – 1.0500 Mg/m ³
Refractive Index @ 25°C	1.5200 – 1.5500 Mg/m ³
Color (ASTM)	4.0 Max.
Viscosity @ 100°C	2.0 – 4.0 mm ² /S
Nitrogen Content	4.0 – 5.0%
Sulfur Content	28.0 – 34.0%
Solubility	Soluble in petroleum and synthetic oils
Flash Point	192 PMCC, °C

Yalub DM86 is ashless oil soluble corrosion inhibitor and metal deactivator for non-ferrous metals. It prevents copper corrosion due to Sulphur.

APPLICATION:

Used in Fuel, Turbine Oil, Compressor Oil, Hydraulic Oil, Engine Oil, Gear Oil, Grease and Metal working fluids.

SHELF LIFE: 24 months.

PACKING AND STORAGE

Available in 25 / 200 kgs. Drum.

To be stored in a clean cool place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

OFFICE

31-H, LAXMI INDL. ESTATE,
NEW LINK ROAD, ANDHERI (W)
MUMBAI 400 053. INDIA
TEL : 91-22-66929152, 66929153, 26310350
FAX : 91 - 22 - 66929154
E-Mail: info@yashoindustries.com
Website: www.yashoindustries.com

FACTORY

PLOT NO.2514-2515,
PHASE IV, G.I.D.C.,
VAPI - 396 195.
GUJARAT, INDIA.
TEL. :- (0260) 2432421 / 2426894
FAX: - (0260) 2410409

Rev. 00 DT. 01.10.2016