

# YALUB TT33

N,N-bis(2-Ethylhexyl)-ar-methyl-  
1H-benzotrizole-1 methanamine

CAS Nr: 94270-86-7

## SALES SPECIFICATION

Appearance	Clear yellowish to brown liquid
Color (ASTM D1500)	L 1.5
Specific Gravity @ 25°C	0.94 – 0.96
Viscosity @ 40°C	20 – 90 cSt
Nitrogen content	13.5 – 15.5%
Moisture	0.2% Max.

## APPLICATION

YALUB TT33 is an oil soluble corrosion inhibitor and metal deactivator for protecting Copper, Copper Alloys, Cadmium, Cobalt, Silver and Zinc. It is mainly used in Fuels, Metal working Fluids, Industrial Lubricants, Greases, Food Grade and Kosher Lubes.

**SHELF LIFE:** 24 months.

## PACKING AND STORAGE

Available in 25 / 200 kgs. Drum.

To be stored in a clean cool place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### YASHO INDUSTRIES PVT. LTD.

#### OFFICE

31-H, LAXMI INDL. ESTATE,  
NEW LINK ROAD, ANDHERI (W)  
MUMBAI 400 053. INDIA  
TEL : 91-22-66929152, 66929153, 26310350  
FAX : 91 - 22 - 66929154  
E-Mail: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website: [www.yashoindustries.com](http://www.yashoindustries.com)

#### FACTORY

PLOT NO.2514-2515,  
PHASE IV, G.I.D.C.,  
VAPI - 396 195.  
GUJARAT, INDIA.  
TEL. :- (0260) 2432421 / 2426894  
FAX: - (0260) 2410409

Rev. 00 DT.01.10.2016