



# YALUB ZDD

**Zinc Diamyldithiocarbamate**

**CAS Nr:** 15337-18-5  
**Emperical Formula:**  $C_{22}H_{44}N_2S_4Zn$   
**Molecular Weight:** 530.25

## SALES SPECIFICATION

Appearance	Amber Liquid
Color (ASTM)	5.0 Max.
Sulfur Content	11.0 – 13.50%
Zinc Content	6.0 – 6.50%
Density @ 25°C	0.9800 – 1.1000 Mg/m <sub>3</sub>
Viscosity @ 100°C	8.0 – 15 cSt
Solubility	Soluble in Synthetic lubricant bases and Petroleum. Insoluble in water
Oil Content	Max. 50%

## APPLICATION

YALUB ZDD is used both as an oxidation inhibitor and metal deactivator in Engine oils, Industrial oils, Lubricating greases, soap clay-thickened greases. It is also used in gasoline and diesel engine crankcase oils.

**SHELF LIFE:** 24 months.

## PACKING AND STORAGE

Available in 25 / 200 kgs. Drum.

To be stored in a clean cool place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### YASHO INDUSTRIES PVT. LTD.

#### OFFICE

31-H, LAXMI INDL. ESTATE,  
NEW LINK ROAD, ANDHERI (W)  
MUMBAI 400 053. INDIA  
TEL : 91-22-66929152, 66929153, 26310350  
FAX : 91 - 22 - 66929154  
E-Mail: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website: [www.yashoindustries.com](http://www.yashoindustries.com)

#### FACTORY

PLOT NO.2514-2515,  
PHASE IV, G.I.D.C.,  
VAPI - 396 195.  
GUJARAT, INDIA.  
TEL. :- (0260) 2432421 / 2426894  
FAX: - (0260) 2410409

Rev. 00 DT.01.10.2016