



YALUB[®] – 3000D

Molybdenum Dithiocarbamate

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Brown liquid
Molybdenum Content	%	9.1 - 11.2
Sulphur Content	%	9.4 - 12.1
Nitrogen Content	%	1.9 – 2.2
Density@ 25 °C	mg/m ³	1.03 - 1.07
Viscosity@100 °C	mm ² /s	50 – 75
Solubility	NA	Soluble in petroleum products. Insoluble in water

PROPERTIES

Uses - Friction reducer and antioxidant for petroleum products. It may also maintain or improve the antifriction properties of engine oil while reducing the phosphorous content.
Not recommended for diesel engine oils.

PACKING AND STORAGE

Available in 200 Kg. Drum
To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713
Phase III, G.I.D.C
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 – 2420896 / 2423896

Rev.02 DT.05.05.2017