

YALUB[®] – 3000D

Molybdenum Dithiocarbamate



SALES SPECIFICATION

| | |
|--------------------|---|
| Appearance | Brown liquid |
| Molybdenum Content | 9.1- 11.2% |
| Sulphur Content | 9.4-12.1 % |
| Nitrogen Content | 1.9 – 2.2 % |
| Density@ 25 °C | 1.03-1.07mg/m ³ |
| Viscosity@ 100 °C | 50-60mm ² /s |
| Solubility | Soluble in petroleum products. Insoluble in water. |

Properties:

Uses - Friction reducer and antioxidant for petroleum products. It may also maintain or improve the antifriction properties of engine oil while reducing the phosphorous content.

Not recommended for diesel engine oils.

Dosage : 0.25 – 0.5%

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

OFFICE

31-H, LAXMI INDL.ESTATE,
NEW LINK ROAD, ANDHERI (W)
MUMBAI 400 053. INDIA
TEL: 91-22-66929152, 66929153,26310350
FAX: 91 - 22 - 66929154
E-Mail: info@yashoindustries.com
Website: www.yashoindustries.com

FACTORY

Plot No.1713, Phase III,
G.I.D.C., Vapi – 396 195
Dist.Bulsar,
GUJARAT, INDIA.
Tel: (0260) 2420896, 2423896
Fax.: (0260)2423996

Rev. DT.18.09.2015