



# YALUB<sup>®</sup> – 525 S

## Molybdenum Dithiocarbamate

### SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Dark Brown Liquid
Molybdenum Content	%	10 – 11
Sulphur Content	%	10.5 – 11.5
Density@ 15 0C	g/cm <sup>3</sup>	1.04 – 1.06
Viscosity@40 0C	mm <sup>2</sup> /s	600 – 800
Flash Point	0C	135

### PROPERTIES

Uses - Friction reducer diesel engine oil, gasoline engine oil, gear oil, metal working fluid, grease.

### PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### YASHO INDUSTRIES PVT. LTD.

#### HEAD OFFICE

Office No. 101 & 102,  
Peninsula Heights,  
C.D.Barfiwala Marg,  
Juhu Lane,  
Andheri (West),  
Mumbai – 400058, India  
TEL : 022 – 62510100  
FAX : 022 – 62510199  
E-Mail.: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website : [www.yashoindustries.com](http://www.yashoindustries.com)

#### FACTORY – UNIT II

Plot No. 1713  
Phase III, G.I.D.C  
Vapi - 396 195,  
Gujarat, India  
TEL. :- 0260 – 2420896 / 2423896

Rev.03 DT.05.05.2017