



YALUB[®] 822 M

Molybdenum Dialkyldithiocarbamate

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Brown liquid
Molybdenum Content	%	4.5 – 5.3
Sulphur Content	%	5.0 – 7.0
Nitrogen Content	%	1.0 – 2.0
Viscosity@ 100 °C	cSt	12.0 –17.0
Density@ 15.6 °C	gm/ml	0.98
Solubility	NA	Soluble in petroleum products. Insoluble in water.

PROPERTIES

Uses - Friction reducer and antioxidant for petroleum products. It may also maintain or improve the anti-friction properties of engine oil while reducing the phosphorous content.

Not recommended for diesel engine oils.

Dosage: 0.2% - 0.6%

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713,
Phase III, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2420896 / 2423896

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.02 DT.01.03.2019