



YALUB[®] – 822 M

Molybdenum Dialkyldithiocarbamate

SALES SPECIFICATION

| PARAMETER | UNIT | REQUIREMENT |
|--------------------|-------|--|
| Appearance | NA | Brown liquid |
| Molybdenum Content | % | 4.5 – 5.3 |
| Sulphur Content | % | 5.0 – 7.0 |
| Nitrogen Content | % | 1.0 – 2.0 |
| Viscosity@100 °C | cSt | 12 – 17 |
| Density@ 15.6 °C | gm/ml | 0.98 |
| Solubility | NA | Soluble in petroleum products. Insoluble in water. |

PROPERTIES

Uses - Friction reducer and antioxidant for petroleum products. It may also maintain or improve the anti-friction properties of engine oil while reducing the phosphorous content. Not recommended for diesel engine oils.

PACKING AND STORAGE

Available in 200 Kg. Drum
To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713
Phase III, G.I.D.C
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 – 2420896 / 2423896

Rev.02 DT.05.05.2017