



# YALUB<sup>®</sup> – 85 M

**Organomolybdenum complex of organic amide**

## **SALES SPECIFICATION**

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Brown liquid
Color 1% in oil	NA	5.0 Max.
Molybdenum Content	%	7.3 – 8.5
Nitrogen Content	%	2.3 – 3.3
Viscosity@ 100 <sup>0</sup> C	cSt	60 – 100
Density@ 20 <sup>0</sup> C	mg/m <sup>3</sup>	1.08 – 1.10
Solubility	NA	Soluble in petroleum products. Insoluble in water.

## **PROPERTIES**

YALUB 85M delivers engine oils with a significant reduction in the coefficient of friction. It is specifically designed for crankcase oils as friction reducer.

This product is not recommended for diesel engine oils.

## **PACKING AND STORAGE**

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### **YASHO INDUSTRIES PVT. LTD.**

#### **HEAD OFFICE**

Office No. 101 & 102,  
Peninsula Heights,  
C.D.Barfiwala Marg,  
Juhu Lane,  
Andheri (West),  
Mumbai – 400058, India  
TEL : 022 – 62510100  
FAX : 022 – 62510199  
E-Mail.: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website : [www.yashoindustries.com](http://www.yashoindustries.com)

#### **FACTORY – UNIT II**

Plot No. 1713  
Phase III, G.I.D.C  
Vapi - 396 195,  
Gujarat, India  
TEL. :- 0260 – 2420896 / 2423896

Rev.02 DT.15.06.2017