

YALUB – DM 86

2,5-dimercapto-1,3,4-thiadiazole derivative

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Clear, amber Liquid
Density @ 15.6°C	mg/m ³	1.04
Color (ASTM)	NA	4
Viscosity @ 100°C	mm ² /S	3.3
Flash Point , PMCC,	⁰ C	192
Nitrogen content	%	4 – 5
Sulfur	%	28 – 34
Solubility	NA	Soluble in petroleum and synthetic oils

PROPERTIES

YALUB DM 86 is used in Fuel, Turbine Oil, Compressor Oil, Hydraulic Oil, Engine Oil, Gear Oil, Grease, Metal working

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 - 2432421 / 2426894 / 2420447

Rev.02 DT.05.05.2017