

YALUB DND

Dinonylated Diphenylamine

CAS RN : 36878-20-3
Empirical Formula : C30H47N
Molecular weight : 422



SALES SPECIFICATION

Appearance	Dark brown viscous Liquid
Sulphur Content	28.5 – 32.0 %
Nitrogen Content	3.2 – 3.8 %
Specific gravity @ 25 °C	0.930 – 0.970 gm/ml
Viscosity @ 40 °C	500 – 900 cSt
Moisture Content	0.50 % Max.
Solubility	Soluble in Petroleum & Synthetic Lubricant base, Insoluble in water.
Flash Point	> 100 °C
Chloride	200 ppm Max

APPLICATION

DND is a liquid general purpose, ashless anti oxidant for industrial oils like hydraulic fluids, turbine oils which are blended with mineral and synthetic base stocks. If also finds application in engine oils, gear oils and greases for automotive, aviation diesel and gas-engine service.

PACKING AND STORAGE

Available in 25 / 200 Kgs Drum

To be stored in a clean cool place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

OFFICE

31-H, LAXMI INDLESTATE,
NEW LINK ROAD, ANDHERI (W)
MUMBAI 400 053. INDIA
TEL : 91-22-66929152, 66929153, 26310350
FAX : 91 - 22 - 66929154
E-Mail: info@yashoindustries.com
Website: www.yashoindustries.com

FACTORY

PLOT NO.2514-2515,
PHASE IV, G.I.D.C.,
VAPI - 396 195.
GUJARAT, INDIA.
TEL. :- (0260) 2432421 / 2426894
FAX: - (0260) 2410409

Rev. DT. DT.01.04.2014