



YALUB DND

Dinonylated diphenylamine

CAS No : 36878-20-3
Empirical Formula : C₃₀H₄₇N
Molecular weight : 422

SALES SPECIFICATIONS

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Dark Brown Viscous Fluid
Density @ 25°C	gm/ml	0.930 – 0.970
Viscosity @ 40°C	cSt	500 -900
Flash Point	°C	> 100
Nitrogen Content	%	3.2 – 3.8
Chlorine Content	ppm	200 Max.
Moisure Content	%	0.50 Max.
Solubility	NA	Soluble in Petroleum and Synthetic Lubricant bases, Insoluble in water.

APPLICATION AND USES

YALUB DND is a liquid general purpose, ashless anti oxidant for industrial oils like hydraulic fluids, turbine oils which are blended with mineral and synthetic base stocks.

It also finds application in engine oils, gear oils and greases for automotive, aviation diesel and gas-engine service.

Applications :

Hydraulic /Break Fluids
Compressor and Circulating Oils
Paper Machine Oils
Industrial and Automotive Gear Oils
Engine oils
Greases
Recycled base Oil

Typical Dosage

0.2% - 0.5%
0.2 % - 0.8 %
0.2 % - 0.5 %
0.2 % - 0.5 %
0.2 % - 0.5 %
0.2 % - 0.6 %
0.1 % - 0.6 %

PACKING AND STORAGE

Available in 25, 200 kgs Drum.

To be stored in a clear, cool and dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 - 2432421 / 2426894 / 2420447