



YALUB LA

Molybdenum di (2-ethylhexyl) phosphorodithioate

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Dark Green Liquid
Molybdenum Content	%	7.7 – 8.8
Sulphur Content	%	11.0 – 13.8
Density (15.6°C)	gm/ml	1.075 – 1.085
Phosphorous Content	%	5.5 – 7.0
Viscosity 100°C	cSt	6 – 10
Solubility	NA	Soluble in petroleum oils and greases, aliphatic & aromatic solvents and in various synthetic lubricants bases. Insoluble in water.

PROPERTIES

Uses - Extreme-pressure, Friction reducer and anti-wear agent used in energy conserving lubricants.

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713
Phase III, G.I.D.C
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 – 2420896 / 2423896

Rev. 03 DT.05.05.2017