



YALUB MDBC

Molybdenum, bis(dibutylcarbamo dithioato)di- μ -oxodioxodi-, sulfurized

CAS No : 68412-26-0
Molecular Formula : C₁₈H₃₆N₂S₄Mo
Molecular weight : 504.68

SALES SPECIFICATIONS:

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Yellow Powder
Density @ 25°C	gm/ml	1.59
Sulphur Content	%	23.5 – 25.5
Molybdenum Content	%	27 – 29
Melting Point	°C	258 Min.
Loss on Drying @ 85 °C.	%	0.2 Max.

APPLICATION AND USES

YALUB MDBC is an Antioxidant, EP & Antiwear Additive for Greases and Industrial oils like hydraulic fluids, turbine oils which are blended with mineral and synthetic base stocks. It also finds application in engine oils, gear oils and greases for automotive, aviation diesel and gas-engine service.

Treat level- 2 - 4% by wt.

PACKING AND STORAGE

Available in 25 Kgs Drum

To be stored in a clear, cool and dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713
Phase III, G.I.D.C
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 – 2420896 / 2423896

Rev. 03 DT.05.05.2017