



YALUB – PA 135

3,5-di-tert-butyl-4-hydroxyhydrocinnamic acid

CAS No. : 125643 -61 -0

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Pale yellow to brownish liquid
Density @ 20 °C	gm/cm ³	0.960 – 0.980
Viscosity at 40 °C	mm ² /s	90 – 150
Flash Point	°C	152 Min.
Solubility	NA	Ester, Mineral oil

PROPERTIES

It is general purpose , non-staining, high molecular weight liquid phenolic antioxidant that provides excellent stability to a wide range of automotive and industrial lubricants. It has excellent solubility in mineral oil and non - conventional base stocks. It is easy to handle and will not crystallize at low temp.

It has low volatility provides superior protection against oxidation & deposit formation.

Dosage :

Industrial Lubricants	0.1 - 0.5 %
Transmission fluid	0.1 - 0.8 %
Metal Working Fluid	0.1 - 0.5 %

PACKING AND STORAGE

Available in 25/200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 - 2432421 / 2426894 / 2420447