

# YALUB – TT 33

**N,N-bis(2-Ethylhexyl)-ar-methyl-1H-benzotrizole-1 methanamine**

## **SALES SPECIFICATION**

<b>PARAMETER</b>	<b>UNIT</b>	<b>REQUIREMENT</b>
Appearance	NA	Clear, yellow to brown liquid
Density at 25 <sup>0</sup> C	gm/ml	0.94 – 0.96
Color (ASTM D 1500)	NA	L 1.5
Viscosity at 40 <sup>0</sup> C	cSt	20 – 90
Viscosity at 100 <sup>0</sup> C	cSt	4 – 6
Flash Point , PMCC	0C	125

## **PROPERTIES**

YALUB TT 33 is an oil soluble corrosion inhibitor and metal deactivator for lubricants, grease and metalworking fluids.

As a corrosion inhibitors, it is effective in protecting copper , copper alloys, cadmium, cobalt , silver and zinc.

As a metal deactivator, YALUB TT 33 inhibits oxidation by chelating metals ions that catalyze oxidation.

## **PACKING AND STORAGE**

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### **YASHO INDUSTRIES PVT. LTD.**

#### **HEAD OFFICE**

Office No. 101 & 102,  
Peninsula Heights,  
C.D.Barfiwala Marg  
Juhu Lane,  
Andheri (West),  
Mumbai – 400058, India  
TEL : 022 – 62510100  
FAX : 022 – 62510199  
E-Mail.: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website : [www.yashoindustries.com](http://www.yashoindustries.com)

#### **FACTORY – UNIT I**

Plot No. 2514/2515,  
Phase IV, G.I.D.C.,  
Vapi - 396 195,  
Gujarat, India  
TEL. :- 0260 - 2432421 / 2426894 / 2420447