



YALUB – ZDD

Zinc Diamyldithiocarbamate

CAS RN : 15337-18-5
Molecular Formula : $C_{22}H_{44}N_2S_4Zn$
Molecular Weight : 530.25

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Amber Liquid
Assay	%	95 Min.
Density at 20 °C	g/ml	0.98
Boiling point	°C	293.7
Viscosity at 100°C	mm ² /s	9.5
Flash Point	°C	131.4
Solubility	NA	Soluble in synthetic lubricant bases & Petroleum. Insoluble in water.
ASTM D-1500	NA	5.0 Max.

PROPERTIES

YALUB ZDD is used in Engine Oils, Industrial Oils, in lubricating greases both as an oxidation inhibitor and metal deactivator, in soap clay-thickened greases. Used in both gasoline and diesel engine crankcase oils to inhibit oxidation, bearing corrosion and wear.

PACKING AND STORAGE

Available in 25 / 200 Kg HDPE Container
To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 - 2432421 / 2426894 / 2420447

Rev.02 DT.05.05.2017