



YAPOX®BHT

(BUTYLATED HYDROXY TOLUENE)

2,6-Di-tert-butyl-4-methylphenol

CAS No. : 128-37-0
Molecular Formula : C₁₅H₂₄O
Molecular Weight : 220

SALES SPECIFICATIONS:

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	White to yellow crystals/flakes
Assay	%	99 Min.
Melting point	°C	69 - 70
Moisture content	%	0.50 Max
Ash Content	%	0.1 Max.

APPLICATION

YAPOX®BHT is used as an Antioxidants for Edible Oils, Lube, Plastic and Resins.

PACKING AND STORAGE

Available in 25 Kg. Paper Bag
To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2432421 / 2426894 / 2420447

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.03 DT.01.03.2019