

YAPOX[®]NT 3164



Benzeneamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

CAS no. : 68411-46-1

Molecular Formula : C₂₀H₂₇N

Molecular weight : 281

TYPICAL SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Pale yellow to reddish brown liquid
Density @ 20°C	gm /cm ³	0.9700 – 0.9800
Kinematic viscosity @ 40°C	mm ² /s	280 – 400
Flash Point	°C	> 185
Nitrogen Content	%	4.0 – 5.0
Solubility	NA	Mineral oil > 5% Ester > 5% Water < 0.01%

APPLICATION & USES

YAPOX[®]NT 3164 imparts good protection against degradation due to heat and oxygen. It has excellent high temperature AO and deposit inhibiting performance. It has low volatility & highly efficient and also prevents thermal degradation of polymers. It is used in elastomers, polyols & polyurethanes.

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2432421 / 2426894 / 2420447

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev. 03 DT.01.03.2019