

YAPOX – PU 55

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Clear liquid
YAPOX PA 135 Content	%	62 – 70
YAPOX BODPA Content	%	30 – 36
Color value APHA	⁰ C	≤ 450

APPLICATION

1) **Polyurethanes** : It prevents free radical formation in polyols during storage & transportation. It is liquid heat stabilizer blend for Polyether & Polyester polyols & Foams. It exhibit good resistance to scorch, fogging & textile staining.

2) **Polyethylene / Polystyrene / Elastomers / Acrylic/ PVC/ ABS/ SBR/ BR/NBR** : It prevents autoxidation giving stability to polymers

Features :

- Non staining , high molecular weight liquid phenolic antioxidant
- Excellent compatibility
- Convenience of a pump able liquid
- Can be added before , during , after processing.
- Low Volatility - The low volatility and excellent compatibility also helps to prevent fogging in automotive applications and to prevent staining of textiles (For Example : Furniture , carpeting, head rests etc). The liquid nature makes it a perfect fit where neat liquids , emulsions, suspension, solutions or melts are an integral part of polymer manufacturing and processing.
- It gives synergetic effect with combination of aminic and phosphatite Antioxidant.

Dosage: 0.15 – 0.5%

PACKING AND STORAGE

Available in 25/ 200 Kgs. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES PVT. LTD.

HEAD OFFICE

Office No. 101 & 102,
Peninsula Heights,
C.D.Barfiwala Marg,
Juhu Lane,
Andheri (West),
Mumbai – 400058, India
TEL : 022 – 62510100
FAX : 022 – 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL. :- 0260 - 2432421 / 2426894 / 2420447