



# YALUB<sup>®</sup>3000 D

**Molybdenum, bis(ditridecylcarbamodithioato)di- $\mu$ -oxodioxo-di-, sulfurized**

EC No.: 948-019-1

## **SALES SPECIFICATION**

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Brown liquid
Molybdenum Content	%	9.1- 11.2
Sulphur Content	%	9.4-12.1
Nitrogen Content	%	1.9 – 2.2
Density@ 25 °C	mg/m <sup>3</sup>	1.030-1.070
Viscosity@100 °C	mm <sup>2</sup> /s	50.0 – 75.0
Solubility	NA	Soluble in petroleum products. Insoluble in water

## **PROPERTIES**

Uses - Friction reducer and antioxidant for petroleum products. It may also maintain or improve the antifriction properties of engine oil while reducing the phosphorous content.  
Not recommended for diesel engine oils.

## **PACKING AND STORAGE**

Available in 200 Kg. Drum  
To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

## **YASHO INDUSTRIES LIMITED**

### **REGISTERED OFFICE**

Office No. 101/102, Peninsula Heights,  
C.D.Barfiwala Marg, Juhu lane,  
Andheri (West), Mumbai – 400058, India  
TEL : +91 22 62510100  
FAX : +91 22 62510199  
E-Mail.: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website : [www.yashoindustries.com](http://www.yashoindustries.com)

### **FACTORY – UNIT II**

Plot No. 1713,  
Phase III, G.I.D.C.,  
Vapi - 396 195,  
Gujarat, India  
TEL.: +91 260 2420896 / 2423896

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.02 DT.01.03.2019