



YALUB[®] 525 S

Molybdenum Dithiocarbamate

SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Dark Brown Liquid
Molybdenum Content	%	10.0–11.0
Sulphur Content	%	10.5 – 12.5
Density@ 15 ⁰ C	gm/cm ³	1.0400 – 1.0800
Viscosity@40 ⁰ C	mm ² /s	600.0 – 800.0
Flash Point	⁰ C	135.0 Min

PROPERTIES

Uses - Friction reducer diesel engine oil, gasoline engine oil, gear oil, metal working fluid, grease.

DOSAGE: 0.25% - 0.5%

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713,
Phase III, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2420896 / 2423896

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.02 DT.01.03.2019