

YALUB[®] B 182



SALES SPECIFICATIONS:

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Clear Yellow to Amber Liquid
Kinematic Viscosity @ 100°C	cSt	4.0 – 7.0
Flash Point	°C	90.0 Min
Specific Gravity @ 15.6°C	g/ml	0.9950 - 1.0350
Zinc Content	%	2.0 – 3.0
Sulphur Content	%	23.5 – 25.5
Phosphorus Content	%	1.0 – 2.5

APPLICATION & USES

YALUB[®] B 182 is carefully formulated to resist degradation of critical grease properties such as drop point and stability in presence of water. This system can be used in a variety of economic-tier multi-purpose greases that require basic EP, Anti-wear and corrosion protection.

BENEFITS

- Excellent EP & Load carrying properties
- Good rust and Wear protection
- High thermal and oxidation stability

RECOMMENDED DOSAGE

The recommended treat rate for YALUB[®] B 182 is 0.5% to 5% (by wt) for typical grease application depending on thickener type and performance level required.

PACKING AND STORAGE:

Available in 25 / 200 kgs Drum.

To be stored in a clear, cool and dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713,
Phase III, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2420896 / 2423896

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.02 DT.01.03.2019