

YALUB[®]B 193

Long-chain alkyl amine



SALES SPECIFICATIONS:

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Clear Yellow to Amber Liquid
Kinematic Viscosity @ 100°C	cst	4.0 – 7.0
Flash Point	°C	100.0 Min
Specific Gravity @ 15.6°C	g/ml	0.9850 – 1.0200
Sulphur Content	%	26.0 – 28.0
Phosphorous Content	%	1.0 – 2.0

APPLICATION & USES

YALUB[®]B 193 additive is a multi-functional gear oil additive based on Sulphur-phosphorous chemistry. YALUB[®]B 193 has been developed for formulating GL-4 transmission lubricant and industrial gear oil and GL-5 hypoid axel lubricants.

FEATURES

- Cost savings at all treats.
- Performance in both industrial and automotive lubricants.
- Trouble free performance.

RECOMMENDED DOSAGE

- 2% (by wt.) – For API GL-4
- 4% (by wt.) – For API GL-5

PACKING AND STORAGE:

Available in 25 / 200 kgs Drum.

To be stored in a clear, cool and dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT II

Plot No. 1713,
Phase III, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2420896 / 2423896

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.02 DT.01.03.2019