



YALUB[®]BO 55

Alkylated Diphenylamine

SALES SPECIFICATION

PARAMETER	UNIT	LIMIT
Appearance	NA	Clear Viscous Yellowish to Reddish Brown Liquid
Viscosity @ 40°C	Cst	450 – 600
Nitrogen Content	%	4.0 – 5.0
Density @ 25°C	gm /cm ³	0.9600 – 0.9800

APPLICATION & USES

Lubricants : It imparts good protection against degradation due to heat and oxygen. Its high nitrogen content and liquid form allow YALUB[®]BO 55 to be easily blended into all types of high performance lubricants. YALUB[®]BO 55 is especially suitable for use in synthetic and mineral oil based lubricant used in high temperature applications. YALUB[®]BO 55 can also be used in synthetic base fluids such as silicone oils & diesters.

PACKING AND STORAGE

Available in 200 Kg. Drum

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,
C.D.Barfiwala Marg, Juhu lane,
Andheri (West), Mumbai – 400058, India
TEL : +91 22 62510100
FAX : +91 22 62510199
E-Mail.: info@yashoindustries.com
Website : www.yashoindustries.com

FACTORY – UNIT I

Plot No. 2514/2515,
Phase IV, G.I.D.C.,
Vapi - 396 195,
Gujarat, India
TEL.: +91 260 2432421 / 2426894 / 2420447

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev. 03 DT.01.03.2019