



# YALUB<sup>®</sup>DM 81

## 2,5-dimercapto-1,3,4-thiadiazole alkyl polycarboxylate

EC No.: 439-050-7

### SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Amber liquid
Density @ 15.6°C	gm/cm <sup>3</sup>	1.090 - 1.150
Viscosity @ 100°C	mm <sup>2</sup> /s	17.0 – 22.0
Nitrogen content	%	5.0 – 7.0
Sulfur content	%	17.0 – 23.0
Flash Point	°C	190.0 Min.
Solubility	NA	Soluble in mineral and synthetic oils formulated with dispersants

### PROPERTIES

YALUB<sup>®</sup>DM 81 is used in Engine oil, Grease.

### PACKING AND STORAGE

Available in 200 Kg. Drum.

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### YASHO INDUSTRIES LIMITED

#### REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,  
C.D.Barfiwala Marg, Juhu lane,  
Andheri (West), Mumbai – 400058, India  
TEL : +91 22 62510100  
FAX : +91 22 62510199  
E-Mail.: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website : [www.yashoindustries.com](http://www.yashoindustries.com)

#### FACTORY – UNIT II

Plot No. 1713,  
Phase III, G.I.D.C.,  
Vapi - 396 195,  
Gujarat, India  
TEL.: +91 260 2420896 / 2423896

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev.02 DT.01.03.2019