



# YALUB<sup>®</sup> PA 15 S

## Thiodiethylene bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate]

CAS No. : 41484-35-9

Molecular formula : C<sub>38</sub>H<sub>58</sub>O<sub>6</sub>S

Molecular weight : 643

### SALES SPECIFICATION

PARAMETER	UNIT	REQUIREMENT
Appearance	NA	Crystalline white to yellow powder
Melting point	<sup>0</sup> C	63 - 74 Min.
Moisture content	%	3.0 Max.
Ash content	%	0.1 Max.
Sulphur content	%	4 – 6

### PROPERTIES

YALUB<sup>®</sup> PA 15 S is high molecular phenolic antioxidant used in hydraulic fluids, metalworking fluids, industrial gear oils, turbine oils, polyglycols, and use with natural and synthetic esters.

### PACKING AND STORAGE

Available in 25 Kg. Paper Bag.

To be stored in a clean, cool & dry place.

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

### YASHO INDUSTRIES LIMITED

#### REGISTERED OFFICE

Office No. 101/102, Peninsula Heights,  
C.D.Barfiwala Marg, Juhu lane,  
Andheri (West), Mumbai – 400058, India  
TEL : +91 22 62510100  
FAX : +91 22 62510199  
E-Mail.: [info@yashoindustries.com](mailto:info@yashoindustries.com)  
Website : [www.yashoindustries.com](http://www.yashoindustries.com)

#### FACTORY – UNIT I

Plot No. 2514/2515,  
Phase IV, G.I.D.C.,  
Vapi - 396 195,  
Gujarat, India  
TEL.: +91 260 2432421 / 2426894 / 2420447

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

Rev. 03 DT.01.03.2019